



PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47574-00005	Date of first issue: 13.01.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : PURELL® Hand sanitising gel VF481™

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Hand Sanitizer

1.3 Details of the supplier of the safety data sheet

Company : GOJO Industries-Europe Ltd.
Units 5 & 6, Stratus Park
MK10 0DE Brinklow, Milton Keynes

Telephone : +44(0) 1908588444

Telefax : +44(0) 1908588445

E-mail address of person responsible for the SDS : infoUK@gojo.com

1.4 Emergency telephone number

+44(0) 8445605135

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting effects.

Classification (67/548/EEC, 1999/45/EC)

Flammable R10: Flammable.

Irritant R36: Irritating to eyes.



Dangerous for the environment R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

PURELL® Hand sanitising gel VF481™

Version 2.0 Revision Date: 03.06.2015 MSDS Number: 47574-00005 Date of last issue: 10.03.2015
Date of first issue: 13.01.2015

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	 
Signal word	:	Warning
Hazard statements	:	H226 Flammable liquid and vapour. H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P337 + P313 If eye irritation persists: Get medical advice/ attention.

2.3 Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Ethanol	64-17-5 200-578-6	F; R11 Xi; R36	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 50 - < 70
Propan-2-ol	67-63-0 200-661-7	F; R11 Xi; R36 R67	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 3 - < 10
Copper Gluconate	527-09-3 208-408-2	Xn; R22 N; R50/53	Acute Tox. 4; H302 Aquatic Acute 1; H400 Aquatic Chronic 1;	>= 0.025 - < 0.1



PURELL® Hand sanitising gel VF481™

Version 2.0	Revision Date: 03.06.2015	MSDS Number: 47574-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015
----------------	------------------------------	-----------------------------	---

			H410	
--	--	--	------	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet



PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47574-00005	Date of first issue: 13.01.2015

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and dis-



PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47574-00005	Date of first issue: 13.01.2015

posal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | |
|-------------------------|--|
| Technical measures | : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : Use with local exhaust ventilation.
Use only in an area equipped with explosion proof exhaust ventilation. |
| Advice on safe handling | : Avoid inhalation of vapour or mist.
Do not swallow.
Do not get in eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice.
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment. |
| Hygiene measures | : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | |
|---|---|
| Requirements for storage areas and containers | : Keep in properly labelled containers. Keep tightly closed.
Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition. |
| Advice on common storage | : Do not store with the following product types:
Strong oxidizing agents
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases |



PURELL® Hand sanitising gel VF481™

Version 2.0 Revision Date: 03.06.2015 MSDS Number: 47574-00005 Date of last issue: 10.03.2015
Date of first issue: 13.01.2015

Explosives
Gases

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Ethanol	64-17-5	OELV - 15 min (STEL)	1,000 ppm	IE OEL
Propan-2-ol	67-63-0	OELV - 8 hrs (TWA)	200 ppm	IE OEL
Further information	Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		OELV - 15 min (STEL)	400 ppm	IE OEL
Further information	Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Ethanol : End Use: Workers
Exposure routes: Inhalation
Potential health effects: Acute local effects
Value: 1900 mg/m3
End Use: Workers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 343 mg/kg bw/day
End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 950 mg/m3
End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Acute local effects
Value: 950 mg/m3
End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 206 mg/kg bw/day
End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 114 mg/m3
End Use: Consumers
Exposure routes: Ingestion

PURELL® Hand sanitising gel VF481™

Version 2.0 Revision Date: 03.06.2015 MSDS Number: 47574-00005 Date of last issue: 10.03.2015
Date of first issue: 13.01.2015

Propan-2-ol

Potential health effects: Long-term systemic effects
Value: 87 mg/kg bw/day

: End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 500 mg/m³
End Use: Workers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 888 mg/kg bw/day
End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 89 mg/m³
End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 319 mg/kg bw/day
End Use: Consumers
Exposure routes: Ingestion
Potential health effects: Long-term systemic effects
Value: 26 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Ethanol

: Fresh water
Value: 0.96 mg/l
Marine water
Value: 0.79 mg/l
Intermittent use/release
Value: 2.75 mg/l
Sewage treatment plant
Value: 580 mg/l
Fresh water sediment
Value: 3.6 mg/kg
Marine sediment
Value: 2.9 mg/kg
Soil
Value: 0.63 mg/kg
Oral
Value: 720 mg/kg

Propan-2-ol

: Fresh water
Value: 140.9 mg/l
Marine water
Value: 140.9 mg/l
Intermittent use/release
Value: 140.9 mg/l
Sewage treatment plant
Value: 2251 mg/l
Fresh water sediment
Value: 552 mg/kg
Marine sediment
Value: 552 mg/kg
Soil
Value: 28 mg/kg

PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47574-00005	Date of first issue: 13.01.2015



Oral
Value: 160 mg/kg

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.
Use only in an area equipped with explosion proof exhaust ventilation.
Use with local exhaust ventilation.

Personal protective equipment

- | | |
|--------------------------|---|
| Eye protection | : Wear the following personal protective equipment:
Safety goggles |
| Hand protection | |
| Material | : Impervious gloves
Flame retardant gloves |
| Remarks | : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. |
| Skin and body protection | : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
Flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc). |
| Respiratory protection | : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. |
| Filter type | : Organic vapour type (A) |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|-----------------|---------------------------|
| Appearance | : liquid |
| Colour | : clear, Hazy, blue green |
| Odour | : alcohol-like |
| Odour Threshold | : No data available |



: 3.5 - 5.2



PURELL® Hand sanitising gel VF481™

Version 2.0 Revision Date: 03.06.2015 MSDS Number: 47574-00005 Date of last issue: 10.03.2015
Date of first issue: 13.01.2015

	Melting point/freezing point	: No data available
	Initial boiling point and boiling range	: 75.00 °C
	Flash point	: 26.5 °C
	Evaporation rate	: No data available
	Flammability (solid, gas)	: Not applicable
	Upper explosion limit	: No data available
	Lower explosion limit	: No data available
	Vapour pressure	: No data available
	Relative vapour density	: No data available
	Density	: 0.8850 g/cm ³
	Solubility(ies)	
	Water solubility	: soluble
	Partition coefficient: n-octanol/water	: Not applicable
	Auto-ignition temperature	: No data available
	Decomposition temperature	: The substance or mixture is not classified self-reactive.
	Viscosity	
	Viscosity, kinematic	: 80 - 600 mm ² /s (20 °C)
	Explosive properties	: Not explosive
	Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.



PURELL® Hand sanitising gel VF481™

Version 2.0 Revision Date: 03.06.2015 MSDS Number: 47574-00005 Date of last issue: 10.03.2015
Date of first issue: 13.01.2015

10.3 Possibility of hazardous reactions

Hazardous reactions : Flammable liquid and vapour.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Ethanol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): 72.6 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Copper Gluconate:

Acute oral toxicity : LD50 (Rat): 1,710 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:



PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47574-00005	Date of first issue: 13.01.2015

Result: No skin irritation

Components:

Ethanol:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Propan-2-ol:

Species: Rabbit
Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Ethanol:

Species: Rabbit
Method: OECD Test Guideline 405
Result: Irritation to eyes, reversing within 21 days

Propan-2-ol:

Species: Rabbit
Result: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.
Respiratory sensitisation: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitisation.

Components:

Ethanol:

Test Type: Local lymph node assay (LLNA)
Exposure routes: Skin contact
Species: Mouse
Result: negative

Propan-2-ol:

Test Type: Buehler Test
Exposure routes: Skin contact
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Ethanol:



PURELL® Hand sanitising gel VF481™

Version 2.0 Revision Date: 03.06.2015 MSDS Number: 47574-00005 Date of last issue: 10.03.2015
Date of first issue: 13.01.2015

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Ingestion
Result: negative

Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Copper Gluconate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Propan-2-ol:

Species: Rat
Application Route: inhalation (vapour)
Exposure time: 104 weeks
Method: OECD Test Guideline 451
Result: negative

Reproductive toxicity

Not classified based on available information.

Components:

Ethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion

PURELL® Hand sanitising gel VF481™

Version 2.0 Revision Date: 03.06.2015 MSDS Number: 47574-00005 Date of last issue: 10.03.2015
Date of first issue: 13.01.2015

||| Result: negative

Copper Gluconate:
||| Effects on fertility : Species: Rat
Application Route: Ingestion
Result: negative

STOT - single exposure

Not classified based on available information.

Components:

Propan-2-ol:

||| Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Ethanol:

||| Species: Rat
NOAEL: 2,400 mg/kg
Application Route: Ingestion
Exposure time: 2 y

Propan-2-ol:

||| Species: Rat
NOAEL: 5000 ppm
Application Route: inhalation (vapour)
Exposure time: 104 w
Method: OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Ethanol:

||| Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l
Exposure time: 96 h

||| Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
aquatic invertebrates Exposure time: 48 h

||| Toxicity to algae : EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

PURELL® Hand sanitising gel VF481™

Version 2.0 Revision Date: 03.06.2015 MSDS Number: 47574-00005 Date of last issue: 10.03.2015
Date of first issue: 13.01.2015

Toxicity to bacteria : EC50 (Photobacterium phosphoreum): 32.1 mg/l
Exposure time: 0.25 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 9.6 mg/l
Exposure time: 9 d
Species: Daphnia magna (Water flea)

Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 10,000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 24 h

Toxicity to bacteria : EC50 (Pseudomonas putida): > 1,050 mg/l
Exposure time: 16 h

Copper Gluconate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.07 - 0.7 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 0.7 - 2.1 mg/l
Exposure time: 48 h

Toxicity to algae : ErC50 (Scenedesmus capricornutum (fresh water algae)): 0.1 - 1 mg/l
Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.1 - 1 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 10

Toxicity to fish (Chronic toxicity) : NOEC: > 1 - 10 µg/l
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 1 - 10 µg/l
Remarks: Based on data from similar materials

M-Factor (Chronic aquatic toxicity) : 10

12.2 Persistence and degradability

Components:

Ethanol:

Biodegradability : Result: Readily biodegradable
Biodegradation: 84 %
Exposure time: 20 d



PURELL® Hand sanitising gel VF481™

Version 2.0 Revision Date: 03.06.2015 MSDS Number: 47574-00005 Date of last issue: 10.03.2015
Date of first issue: 13.01.2015

||

Propan-2-ol:

||

Biodegradability : Result: rapidly degradable

12.3 Bioaccumulative potential

Components:

Ethanol:

||

Partition coefficient: n-octanol/water : log Pow: -0.35

Propan-2-ol:

||

Partition coefficient: n-octanol/water : log Pow: 0.05

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1987
ADR : UN 1987
RID : UN 1987
IMDG : UN 1987
IATA : UN 1987



PURELL® Hand sanitising gel VF481™

Version 2.0 Revision Date: 03.06.2015 MSDS Number: 47574-00005 Date of last issue: 10.03.2015
Date of first issue: 13.01.2015

14.2 UN proper shipping name

ADN : ALCOHOLS, N.O.S.
(Ethanol, Propan-2-ol)

ADR : ALCOHOLS, N.O.S.
(Ethanol, Propan-2-ol)

RID : ALCOHOLS, N.O.S.
(Ethanol, Propan-2-ol)

IMDG : ALCOHOLS, N.O.S.
II (Ethanol, Propan-2-ol)

IATA : Alcohols, n.o.s.
(Ethanol, Propan-2-ol)

14.3 Transport hazard class(es)

ADN : 3

ADR : 3

RID : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-D

IATA
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344



PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47574-00005	Date of first issue: 13.01.2015

Packing group : III
 Labels : Flammable Liquids

14.5 Environmental hazards

ADN
 Environmentally hazardous : no

ADR
 Environmentally hazardous : no

RID
 Environmentally hazardous : no

IMDG
 Marine pollutant : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

6	Flammable.	Quantity 1 5,000 t	Quantity 2 50,000 t
---	------------	-----------------------	------------------------

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c	FLAMMABLE LIQUIDS	5,000 t	50,000 t
-----	-------------------	---------	----------

34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil	2,500 t	25,000 t
----	--	---------	----------



PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47574-00005	Date of first issue: 13.01.2015

blending streams),(d)
heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: < 75 %

The components of this product are reported in the following inventories:

AICS : All ingredients listed or exempt.

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of R-Phrases

R11 : Highly flammable.
R22 : Harmful if swallowed.
R36 : Irritating to eyes.
R50/53 : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67 : Vapours may cause drowsiness and dizziness.

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H302 : Harmful if swallowed.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Acute aquatic toxicity
Aquatic Chronic : Chronic aquatic toxicity
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
STOT SE : Specific target organ toxicity - single exposure



PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47574-00005	Date of first issue: 13.01.2015

IE OEL : Ireland. List of Chemical Agents and Occupational Exposure Limit Values - Schedule 1

IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)

IE OEL / OELV - 15 min (STEL) : Occupational exposure limit value (15-minute reference period)

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

IE / EN